



Network

PTZ

# QNP-6250

2MP PTZ Camera



## Key Features

- Max. 2MP resolution
- 4.44~111mm(25x) lens
- Day & Night (ICR), WDR, DIS (Built-in gyro sensor)
- Intelligent Analytics
- H.264, H.265, MJPEG codec, WiseStreamII
- Micro SD/SDHC/SDXC 1slot 256GB

## Compatible Devices

---



SHP-1520FW

SBP-301HMW3

# QNP-6250

2MP PTZ Camera



## Specifications

### Video

|                         |   |                        |
|-------------------------|---|------------------------|
| Imaging Device          | Size  | 1/2.8"                 |
|                         | Type  | CMOS                   |
| Resolution              | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |                        |
| Max. Framerate          | H.265/H.264   | 60fps/50fps(60Hz/50Hz) |
|                         | MJPEG   | 30fps                  |
| Min. Illumination (Lux) | Color(1/30sec, 30IRE)   | 0.05                   |
|                         | BW(1/30sec, 30IRE)  | 0.005                  |

### Lens

|                               |                        |              |
|-------------------------------|------------------------|--------------|
| Focal Length (mm)             | 4.44~111               |              |
| Zoom Ratio                    | Optical                | 25x          |
|                               | Digital                | 32x          |
| Max Aperture Ratio (F number) | Wide                   | 1.6          |
|                               | Tele                   | 3.9          |
| Angular Field of View         | Horizontal             | 64.66°~2.99° |
|                               | Vertical               | 38.08°~1.68° |
| Min. Object Distance          | 1.5m(4.92ft)           |              |
| Focus Control                 | Oneshot AF, Focus save |              |
| Lens Type                     | DC auto iris           |              |

### Pan / Tilt / Rotate

|                           |   |                     |
|---------------------------|---|---------------------|
| Pan / Tilt / Rotate Range | Pan   | 360° Endless        |
|                           | Tilt  | 90°~15°             |
| Pan Speed                 | Preset  | Max. 700°/sec       |
|                           | Manual  | 0.024°/sec~200°/sec |
| Tilt Speed                | Preset  | Max. 300°/sec       |
|                           | Manual  | 0.024°/sec~200°/sec |
| Sequence                  | Preset(300ea), Swing, Group(6ea), Trace, Tour, Auto Run, Schedule |                     |
| Preset Accuracy           | ±0.2°   |                     |

## Operational

|  |                |   |
|--|----------------|---|
| Direction Indicator                      |                | Support   |
| Day & Night                              |                | Auto(ICR)   |
| Backlight Compensation                   |                | BLC, HLC, WDR, SSSR   |
| Wide Dynamic Range (dB)                  |                | 120   |
| Digital Noise Reduction                  |                | SSNR V  |
| Digital Image Stabilization              |                | Support(built-in gyro sensor)   |
| Defog                                    |                | Support   |
| Motion Detection                         | Quantity       | 8ea   |
|  | Shape          | 8point Polygonal zones  |
| Privacy Masking                          | Quantity       | 32ea  |
|  | Shape          | 4point Quadrangle zones   |
|  | Color / Option | Gray, Green, Red, Blue, Black, White, Mosaic  |
| Gain Control                             |                | Off, Max gain, Manual   |
| White Balance                            |                | ATW, AWC, Manual, Indoor, Outdoor, Mercury, Sodium  |
| Electronic Shutter                       | Mode           | Minimum, Maximum, Anti flicker  |
|  | Speed Range    | 2~1/12,000sec   |
| Video Rotation                           |                | Flip&Mirror   |
| Alarm Interface                          | In/Out         | Input 4ea / Output 2ea  |
| Alarm Triggers                           |                | Analytics, Network disconnect, Alarm input  |
| Alarm Events When Alarm Trigger Occurred |                | File upload(image): e-mail/FTP,<br>Notification: e-mail,<br>Recording: SD/SDHC/SDXC or NAS recording at event triggers.Alarm output,<br>Handover: PTZ preset,send message by HTTP/HTTPS/TCP |
| Audio In                                 |                | Selectable(mic in/line in)  |
| Audio Out                                |                | Line out  |
| Auto Tracking                            |                | Support   |

## Analytics

|                  |        |  |
|------------------|--------|--|
| Analytics Events | Normal | Motion detection, Tampering, Audio detection, Virtual area(Lotering, Intrusion, Enter/Exit, Appear/Disappear), Virtual line(Crossing, Direction) |
|------------------|--------|--|

## Network

|                   |   |
|-------------------|---|
| Ethernet          | RJ-45(10/100BASE-T)   |
| Video Compression | H.265/H.264: Main/High, MJPEG   |
| Audio Compression | G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz,<br>G.726: 16kbps,24kbps,32kbps,40kbps,<br>AAC-LC: 48kbps at 16kHz |
| Smart Codec       | Manual, WiseStream II   |
| Bitrate Control   | H.265/H.264: CBR or VBR,<br>MJPEG: VBR  |

## Network

|                                   |                    |  |
|-----------------------------------|--------------------|--|
| Streaming                         | Unicast            | Up to 20 users   |
|                                   | Multicast          | Support  |
|                                   | Multiple Streaming | Up to 10 profiles  |
| Protocol                          |                    | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), NTCIP 1205 |
| Application Programming Interface | ONVIF              | S, G, T  |
|                                   | Others             | SUNAPI(HTTP API), Hanwha Vision Open Platform  |
| Direct Cloud Connection           |                    | Optional (needs gateway)   |

## Security

|                        |   |  |
|------------------------|---|--|
| OS / Firmware Protect  | Encrypted firmware  |  |
| User authentication    | Digest authentication, Prevent brute-force attack                       |  |
| Network authentication | IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)                      |  |
| Secure Communication   | HTTPS, WSS(WebSocket Secure), SRTP                                      |  |
| Access Control         | IP-based access control   |  |
| Data Protect           | Encryption credentials, Encrypt compress for live recording file export |  |
| Audit                  | Access / System / Event Log management                                  |  |
| Device ID              | Device certificate(Hanwha Vision Root CA)                               |  |

## General

|              |                    |                    |
|--------------|--------------------|--------------------|
| Memory       | RAM                | 1GB                |
|              | Flash              | 256MB              |
| Edge Storage | Micro SD/SDHC/SDXC | Max. 256GB x 1slot |

## Environmental & Electrical

|                     |                           |                           |
|---------------------|---------------------------|---------------------------|
| Operating Condition | Temperature               | -10°C~+55°C(+14°F~+131°F) |
|                     | Humidity                  | 0~95% RH(non-condensing)  |
| Storage Condition   | Temperature               | -30°C~+60°C(-22°F~+140°F) |
|                     | Humidity                  | 0~95% RH(non-condensing)  |
| Input Voltage       | PoE+(IEEE802.3at, Class4) |                           |
| Power Consumption   | PoE                       | Max 14.5W, Typical 12W    |

## Mechanical

|                    |                         |  |
|--------------------|-------------------------|--|
| Color              | White                   |  |
| Material           | Plastic                 |  |
| RAL Code           | RAL9003                 |  |
| Product Dimensions | ø152x218mm(ø5.98x8.58") |  |
| Product Weight     | 1700g(3.75lb)           |  |

## Certifications & Standards

|             |  |
|-------------|--|
| EMC         | FCC 47 CFR 15 Subpart B Class A, CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS-NZS CISPR 32 Class A, IC Regulation ICES-003 Issue 7 Class A |
| Safety      | UL 62368-1, CAN/CSA C22.2 NO. 62368-1  |
| Environment | IEC/EN 63000   |

## DORI (EN62676-4 standard)

|                           |      |                   |
|---------------------------|------|-------------------|
| Detect (25PPM/ 8PPF)      | Wide | 60.7m(199.1ft)    |
|                           | Tele | 1471.3m(4827.2ft) |
| Observe (63PPM/ 19PPF)    | Wide | 24.3m(79.6ft)     |
|                           | Tele | 588.5m(1930.9ft)  |
| Recognize (125PPM/ 38PPF) | Wide | 12.1m(39.8ft)     |
|                           | Tele | 294.3m(965.4ft)   |
| Identify (250PPM/ 76PPF)  | Wide | 6.1m(19.9ft)      |
|                           | Tele | 147.1m(482.7ft)   |

# QNP-6250

2MP PTZ Camera



## CAD

Unit: mm [inch]

